



```
seaf-cli list-remote -s https://box.nju.edu.cn -u <username>
```

5.   ID

```
seaf-cli sync -s https://box.nju.edu.cn -u <username> -l <library-id> -d <folder>
```

```
seaf-cli download -s https://box.nju.edu.cn -u <username> -l <library-id> -d <folder>
```

6.

```
seaf-cli status
```

7.

```
seaf-cli desync -d <folder>
```

8.

```
seaf-cli stop
```

Linux

- seadrive  Linux
- seadrive-gui

1.  Token

```
curl -d 'username=<username>' -d 'password=<password>' https://box.nju.edu.cn/api2/auth-token/
```

2. `~~~~~` `~/seadrive.conf` `<username>` `~~~~~` `<token>` `~~~~~`

```
[account]
server = https://box.nju.edu.cn
username = <username>
token = <token>
is_pro = true
[general]
client_name = mypc
[cache]
size_limit = 10GB
clean_cache_interval = 10
```

3. `~~~~~`

```
seadrive -c ~/seadrive.conf -f -d ~/.seadrive/data -l ~/.seadrive/data/logs/seadrive.log ~/SeaDrive
```

4. `~~~~` `Transport endpoint is not connected` `~~~~` `fusermount -u ~/SeaDrive`

5. `~/SeaDrive` `~~~~~`

---

Revision #5

Created 3 June 2021 11:14:12 by Yao Ge

Updated 24 September 2022 17:06:05 by Yao Ge