特别篇： Linux 图形与命令行客户端

同步客户端
安装

参考 官方文档 安装 Linux同步客户端，我们的镜像站提供了客户端的 本地镜像 。同步客户端命令行界面： seaf-cli（ Linux命令行客户端手册 ）
同步客户端图形化界面： seafile-applet

命令行使用

1. 创建客户端本地数据目录（目录名可更改）
mkdir ~/Seafile
2. 初始化客户端并指定本地数据目录（上一步创建的目录）
seaf-cli init -d ~/Seafile
3. 启动客户端
seaf-cli start

4. 列出云盘资料库 ID（ <username>替换为账号）

```
seaf-cli list-remote -s https://box.nju.edu.cn -u <username>
```

5. 将本地目录与云盘资料库同步（`<library-id>`替换为上一步列出的某个资料库ID，`<folder>`替换为本地目录）

```
seaf-cli sync -s https://box.nju.edu.cn -u <username> -l <library-id> -d <folder>
```

将云盘资料库下载到本地目录

```
seaf-cli download -s https://box.nju.edu.cn -u <username> -l <library-id> -d <folder>
```

6. 查看当前同步状态

```
seaf-cli status
```

7. 解除本地目录同步

```
seaf-cli desync -d <folder>
```

8. 停止客户端

```
seaf-cli stop
```

挂载盘客户端

安装

参考 官方文档安装 Linux挂载盘客户端，我们的镜像站提供了客户端的本地镜像。

- 挂载盘客户端命令行界面: seadrive（Linux命令行挂载盘手册）
- 挂载盘客户端图形化界面: seadrive-gui

命令行使用

1. 获取 Token（`<username>`替换为账号，`<password>`替换为密码）

```
curl -d 'username=<username>' -d 'password=<password>'
https://box.nju.edu.cn/api2/auth-token/
```

2. □□□□□□ `~/seadrive.conf` □ `<username>` □□□□□□ `<token>` □□□□□□□□□□

```
[account]
server = https://box.nju.edu.cn
username = <username>
token = <token>
is_pro = true
[general]
client_name = mypc
[cache]
size_limit = 10GB
clean_cache_interval = 10
```

3. □□□□□□□□□□□□□□□□□□□□□□□□□□□□

```
seadrive -c ~/seadrive.conf -f -d ~/.seadrive/data -l
~/.seadrive/data/logs/seadrive.log ~/SeaDrive
```

4. □□□□ `Transport endpoint is not connected` □□□□ `fusermount -u ~/SeaDrive`

5. `~/SeaDrive` □□□□□□□□□□□□□□□□□□□□□□□□

Revision #5
Created 2021-06-03 11:14:12 CST by Yao Ge
Updated 2022-09-24 17:06:05 CST by Yao Ge