

RoseTTAFold

/fs00/software/rosettafold/1.1.0

□□ aptainer □□ bind□□ home □□□□□□□□ RoseTTAFold □□ folding □ conda
□□□□□□□□□□□□□□□□□□□□ --no-home □□□□□□□□

```
#BSUB -J RoseTTAFold
#BSUB -q gpu
#BSUB -n 8
#BSUB -gpu num=1

##### Configurie Numpy threads #####

export OMP_NUM_THREADS="$LSB_DJOB_NUMPROC"
export MKL_NUM_THREADS="$LSB_DJOB_NUMPROC"

##### Definition #####

ROSETTAFOLD_DATADIR=/fsb/data/rosettafold      # path to RoseTTAFold data (host)
ROSETTAFOLD_IMAGE=RoseTTAFold-1.1.0.sif      # path to RoseTTAFold image (host)
ROSETTAFOLD_APPDIR=/app/RoseTTAFold          # path to RoseTTAFold working directory
(container)

##### Database #####

UNIREF30_DB=$ROSETTAFOLD_DATADIR/UniRef30_2020_06
BFD_DB=$ROSETTAFOLD_DATADIR/bfd
PDB100_DB=$ROSETTAFOLD_DATADIR/pdb100_2021Mar03

##### Example #####

RUN_ROSETTAFOLD="aptainer run --bind $UNIREF30_DB:$ROSETTAFOLD_APPDIR/UniRef30_2020_06 \
--bind $BFD_DB:$ROSETTAFOLD_APPDIR/bfd \
--bind $PDB100_DB:$ROSETTAFOLD_APPDIR/pdb100_2021Mar03 \
--nv $ROSETTAFOLD_IMAGE"
```

```
# For monomer structure prediction (e2e)
${RUN_ROSETTAFOLD} $ROSETTAFOLD_APPDIR/run_e2e_ver.sh $ROSETTAFOLD_APPDIR/example/input.fa
output/

# For monomer structure prediction (pyrosetta)
${RUN_ROSETTAFOLD} $ROSETTAFOLD_APPDIR/run_pyrosetta_ver.sh
$ROSETTAFOLD_APPDIR/example/input.fa output/

# For complex modeling
${RUN_ROSETTAFOLD} python $ROSETTAFOLD_APPDIR/network/predict_complex.py \
    -i $ROSETTAFOLD_APPDIR/example/complex_modeling/paired.a3m \
    -o output/ -Ls 218 310

# For PPI screening using faster 2-track version (example input and output are at
example/complex_2track)
${RUN_ROSETTAFOLD} python $ROSETTAFOLD_APPDIR/network_2track/predict_msa.py \
    -msa $ROSETTAFOLD_APPDIR/example/complex_2track/input.a3m \
    -npz output/complex.npz -L1 218
```

Revision #3

Created 2024-11-18 19:15:43 CST by LadderOperator

Updated 2025-03-13 23:55:17 CST by Yao Ge